# NSN 5320-01-502-9838

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-502-9838



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.5025 inches and 0.5225 inches

#### Head Style:

Flush countersunk

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.2021 inches and 0.2026 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.297 inches and 0.302 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

0.1875 inches

Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

2000 pounds per square inch

## **Thread Size:**

0.190 inches

# Shear Strength:

95000 single pounds per square inch

## Countersink Angle:

100.0 degrees

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams-4928 assn standard single material response or ams-4967 assn standard single material response

## Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-502-9838

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

