

View Online at <https://aerobasegroup.com/nsn/5320-01-504-0497>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.690 inches and 2.710 inches

Head Style:

Err-090

Head Height:

Between 0.228 inches and 0.238 inches

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.918 inches and 0.953 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Aircraft, thunderbolt ii, a-10

Grip Length:

Between 1.870 inches and 1.880 inches

Thread Size:

0.625 inches

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Ams 6415 assn standard single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.