

View Online at <https://aerobasegroup.com/nsn/5320-01-504-0497>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.690 inches and 2.710 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.228 inches and 0.238 inches

**Width Between Flats:**

Between 0.2520 inches and 0.2555 inches

**Shank Diameter:**

Between 0.6230 inches and 0.6240 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.918 inches and 0.953 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

Aircraft, thunderbolt ii, a-10

**Grip Length:**

Between 1.870 inches and 1.880 inches

**Thread Size:**

0.625 inches

**Material:**

Steel comp 4340 or steel comp 8740

**Material Specification:**

Ams 6415 assn standard single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.