## NSN 5320-01-504-0508

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-504-0508 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.687 inches and 2.707 inches **Head Style:** Err-090 **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.4360 inches and 0.4370 inches **Shank Style: Head Major Diameter:** Between 0.592 inches and 0.627 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** Aircraft, thunderbolt ii, a-10 **Grip Length:** Between 2.057 inches and 2.067 inches **Thread Size:** 0.438 inches Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Ams 6415 assn standard single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-504-0508

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.