

View Online at <https://aerobasegroup.com/nsn/5320-01-504-0508>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.687 inches and 2.707 inches

Head Style:

Err-090

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

Between 0.1895 inches and 0.1930 inches

Shank Diameter:

Between 0.4360 inches and 0.4370 inches

Shank Style:

Head Major Diameter:

Between 0.592 inches and 0.627 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Aircraft, thunderbolt ii, a-10

Grip Length:

Between 2.057 inches and 2.067 inches

Thread Size:

0.438 inches

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Ams 6415 assn standard single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.