
# NSN 5320-01-504-0508

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.687 inches and 2.707 inches

### Head Style:

Err-090

#### Head Height:

Between 0.150 inches and 0.160 inches

### Width Between Flats:

Between 0.1895 inches and 0.1930 inches

#### Shank Diameter:

Between 0.4360 inches and 0.4370 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.592 inches and 0.627 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## End Application:

Aircraft, thunderbolt ii, a-10

# Grip Length:

Between 2.057 inches and 2.067 inches

### **Thread Size:**

0.438 inches

### Material:

Steel comp 4340 or steel comp 8740

### **Material Specification:**

Ams 6415 assn standard single material response or mil-s-6049 military specification single material response

### Surface Treatment:

Cadmium

### Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

### Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-504-0508

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

