## NSN 5320-01-504-2327

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-504-2327



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.445 inches and 0.455 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.045 inches and 0.055 inches

#### Width Between Flats:

Between 0.079 inches and 0.080 inches

#### Shank Diameter:

0.202 inches

Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.120 inches and 0.130 inches

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

2500 pounds per square inch

#### Thread Size:

1.000 inches

#### Shear Strength:

6130 double pounds per square inch

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-504-2327

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

