

View Online at <https://aerobasegroup.com/nsn/5320-01-504-2906>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.385 inches and 2.405 inches

Head Style:

Err-090

Head Height:

Between 0.200 inches and 0.210 inches

Width Between Flats:

Between 0.2520 inches and 0.2555 inches

Shank Diameter:

Between 0.5917 inches and 0.5927 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.870 inches and 0.905 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Aircraft, stratolifter c-135

Grip Length:

Between 1.620 inches and 1.630 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

0.5625 inches

Shear Strength:

52400 double pounds per square inch

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.