

View Online at <https://aerobasegroup.com/nsn/5320-01-504-4927>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.425 inches and 1.445 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.4985 inches and 0.4995 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.717 inches and 0.770 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

C-135 aircraft

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Threads are color coded black

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0