## NSN 5320-01-504-9598

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-504-9598 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.620 inches and 2.645 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.589 inches and 0.725 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 1.011 inches and 1.094 inches **Tip Diameter:** Between 0.616 inches and 0.623 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.990 inches and 2.005 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 0.625 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5320-01-504-9598

Pin-rivet - Page 2 of 2



Fiig:

A528u0