# NSN 5320-01-504-9600

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-504-9600

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 2.620 inches and 2.645 inches

#### Head Style:

Flush countersunk

#### Shank Diameter:

0.654 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.978 inches and 1.060 inches

#### Tip Diameter:

Between 0.616 inches and 0.623 inches

#### Lubrication:

Cetyl alcohol

#### Grip Length:

Between 1.990 inches and 2.005 inches

### Thready Qty Per Inch (tpi):

18

#### Thread Size:

0.623 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No



# NSN 5320-01-504-9600

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

