# NSN 5320-01-504-9601

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-504-9601



#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 2.715 inches and 2.740 inches

# Head Style:

Flush countersunk

## Shank Diameter:

Between 0.723 inches and 0.759 inches

## Shank Style:

Pin-rivet, tapered, threaded

## Head Major Diameter:

Between 1.044 inches and 1.128 inches

## Tip Diameter:

Between 0.616 inches and 0.623 inches

#### Lubrication:

Cetyl alcohol

#### Grip Length:

Between 1.990 inches and 2.005 inches

## Thready Qty Per Inch (tpi):

18

## Thread Size:

0.625 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

## Material Specification:

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

## Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-504-9601

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

