NSN 5320-01-504-9614

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-504-9614 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.568 inches and 1.583 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.417 inches and 0.437 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.577 inches and 0.630 inches **Tip Diameter:** Between 0.368 inches and 0.373 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.115 inches and 1.130 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-504-9614

Pin-rivet - Page 2 of 2



Fiig:

A528u0