# NSN 5320-01-504-9620

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-504-9620



#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 1.693 inches and 1.708 inches

# Head Style:

Flush countersunk

### Shank Diameter:

Between 0.414 inches and 0.437 inches

## Shank Style:

Pin-rivet, tapered, threaded

## Head Major Diameter:

Between 0.577 inches and 0.630 inches

# Tip Diameter:

Between 0.368 inches and 0.373 inches

## Lubrication:

Cetyl alcohol

# Grip Length:

Between 1.240 inches and 1.255 inches

# Thready Qty Per Inch (tpi):

24

### Thread Size:

0.375 inches

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-504-9620

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

