# NSN 5320-01-504-9621

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-504-9621



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.708 inches and 1.733 inches

## Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.382 inches and 0.405 inches

### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.546 inches and 0.598 inches

#### Tip Diameter:

Between 0.368 inches and 0.373 inches

#### Lubrication:

Cetyl alcohol

## Grip Length:

Between 1.303 inches and 1.318 inches

## Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-01-504-9621

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

