
# NSN 5320-01-504-9626

Pin-rivet - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.771 inches and 1.796 inches

# Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.380 inches and 0.405 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.546 inches and 0.598 inches

#### **Tip Diameter:**

Between 0.368 inches and 0.373 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

Between 1.365 inches and 1.380 inches

#### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-504-9626

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

