NSN 5320-01-504-9631

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-504-9631



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.943 inches and 1.968 inches

Head Style:

Flush countersunk

Shank Diameter:

Between 0.409 inches and 0.437 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

Between 0.577 inches and 0.630 inches

Tip Diameter:

Between 0.368 inches and 0.373 inches

Lubrication:

Cetyl alcohol

Grip Length:

Between 1.490 inches and 1.505 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-504-9631

Pin-rivet - Page 2 of 2

Fiig: A528u0

