NSN 5320-01-504-9734

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-504-9734 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.193 inches and 2.218 inches **Head Style:** Flush countersunk **Shank Diameter:** Between 0.458 inches and 0.491 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.658 inches and 0.729 inches **Tip Diameter:** Between 0.429 inches and 0.436 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.740 inches and 1.755 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.438 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5320-01-504-9734

Pin-rivet - Page 2 of 2



Fiig:

A528u0