
# NSN 5320-01-504-9737

Pin-rivet - Page 1 of 2





### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.225 inches and 2.250 inches

## Head Style:

Flush countersunk

#### Shank Diameter:

Between 0.477 inches and 0.509 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.676 inches and 0.748 inches

#### Tip Diameter:

Between 0.429 inches and 0.436 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

Between 1.740 inches and 1.755 inches

#### Thready Qty Per Inch (tpi):

20

#### Thread Size:

0.438 inches

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response

#### Surface Treatment:

Cadmium

#### Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

# NSN 5320-01-504-9737

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

