

View Online at <https://aerobasegroup.com/nsn/5320-01-505-0894>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3422 inches and 0.3432 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

End Application:

A-10

Grip Length:

Between 1.370 inches and 1.380 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.3125 inches

Shear Strength:

17600 double pounds per square inch

Countersink Angle:

100.0 degrees

Product Name:

Pincots item

Special Features:

Non-lubed pins must be used with wet sealant or lubed collar

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.