NSN 5320-01-505-0942



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-505-0942 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** A-10 **Grip Length:** Between 1.870 inches and 1.880 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Shear Strength:** 49100 double pounds per square inch **Product Name:** Pincots item Material: Steel comp xm-13 **Material Specification:** Qq-p-416, type2, class2 federal specification single treatment response

Ams 5629 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification: Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-505-0942

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0