NSN 5320-01-505-0942

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-505-0942

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Head Style: |
| Err-090 |
| Head Height: |
| Between 0.178 inches and 0.188 inches |
| Width Between Flats: |
| Between 0.2207 inches and 0.2242 inches |
| Shank Diameter: |
| Between 0.4985 inches and 0.4995 inches |
| Shank Style: |
| Pin-rivet, straight, threaded |
| Head Major Diameter: |
| Between 0.735 inches and 0.770 inches |
| Lubrication: |
| Cetyl alcohol, specification 305, hi-shear corp |
| End Application: |
| A-10 |
| Grip Length: |
| Between 1.870 inches and 1.880 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Thread Size: |
| 0.500 inches |
| Shear Strength: |
| 49100 double pounds per square inch |
| Product Name: |
| Pincots item |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type2, class2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| |

NSN 5320-01-505-0942

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

