# NSN 5320-01-505-5266

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-505-5266

## Fastener Length:

Between 0.865 inches and 0.885 inches

#### Head Style:

Undersized oval countersunk

# Head Height:

Between 0.004 inches and 0.007 inches

#### Shank Diameter:

Between 0.186 inches and 0.188 inches

#### Shank Style:

Straight

Head Major Diameter:

Between 0.293 inches and 0.298 inches

#### Head Minor Diameter:

Between 0.198 inches and 0.208 inches

#### **Countersink Height:**

Between 0.052 inches and 0.055 inches

#### **End Application:**

Missle, air launch cruise

#### **Countersink Angle:**

100.0 degrees

#### **Product Name:**

Rivet

# Material:

Aluminum alloy 5056

#### **Material Specification:**

Qq-a-430 federal specification single material response

#### Surface Treatment:

Chromate

## Surface Treatment Specification:

Mil-c-5541, class 1a, clear, colorless military specification 1st treatment response

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

# Fiig:

A040a0

#### Mil-std (military Standard):

Mil-c-5541 spec.