NSN 5320-01-505-9238

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-505-9238

Fastener Length:
0.263 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.155 inches and 0.159 inches
Shank Style:
Self-plugging mechanically locked stem
Head Major Diameter:
Between 0.282 inches and 0.290 inches
Expansion Device:
Serrated stem-type w
End Application:
Aircraft, hornet f/a-18 (e/f)
Grip Length:
Between 0.063 inches and 0.125 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
For the fully serrated spindle series the lock ring may be intregal with the sleeve in which case the lock ring is of the same material and finish
as the sleeve
Material:
Aluminum alloy 2017 sleeve
Material Specification:
Qq-a-430 federal specification single material response stem
Surface Treatment:
Anodize stem or chromate stem
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response stem or mil-c-5541 military specification single treatment response stem
Specification Data:
80205-nas1399 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0
Mil-std (military Standard):

Mil-a-8625 spec.