NSN 5320-01-505-9299



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-505-9299 **Fastener Length:** 0.451 inches **Head Style:** Universal **Head Height:** Between 0.067 inches and 0.077 inches **Shank Diameter:** Between 0.155 inches and 0.159 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.296 inches and 0.328 inches **Expansion Device:** Serrated stem-type w **End Application:** Aircraft, hornet f/a-18 (e/f) **Grip Length:** Between 0.251 inches and 0.312 inches **Special Features:** For the fully serrated spindle series the lock ring may be intregal with the sleeve in which case the lock ring is of the same material and finish as the sleeve Material: Aluminum alloy 2017 sleeve **Material Specification:** Qq-a-430 federal specification single material response stem **Surface Treatment:** Anodize stem or chromate stem **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response stem or mil-c-5541 military specification single treatment response stem **Specification Data:** 80205-nas1398 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Mil-std (military Standard):

Mil-a-8625 spec.

Fiig: A040a0