Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-505-9300

Fastener Length:

0.388 inches

Head Style:

Universal

Head Height:

Between 0.067 inches and 0.077 inches

Shank Diameter:

Between 0.155 inches and 0.159 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.296 inches and 0.328 inches

Expansion Device:

Serrated stem-type w

End Application:

Aircraft, hornet f/a-18 (e/f)

Grip Length:

Between 0.188 inches and 0.250 inches

Special Features:

For the fully serrated spindle series the lock ring may be intregal with the sleeve in which case the lock ring is of the same material and finish

as the sleeve

Material:

Aluminum alloy 2017 sleeve

Material Specification:

Qq-a-430 federal specification single material response stem

Surface Treatment:

Anodize stem or chromate stem

Surface Treatment Specification:

Mil-a-8625 military specification single treatment response stem or mil-c-5541 military specification single treatment response stem

Specification Data:

80205-nas1398 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.