NSN 5320-01-506-5121

View Online at https://aerobasegroup.com/nsn/5320-01-506-5121

Pin-rivet - Page 1 of 2

Unjf

N/a

Shelf Life:



Thread Class: За **Thread Direction:** Right-hand **Head Style:** Err-090 **Head Height:** Between 0.098 inches and 0.112 inches Width Between Flats: Between 0.160 inches and 0.180 inches **Shank Diameter:** Between 0.3422 inches and 0.3432 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.490 inches and 0.520 inches **End Application:** A-10 **Grip Length:** Between 1.1325 inches and 1.4425 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.3125 inches **Shear Strength:** 17600 double pounds per square inch **Product Name:** Rivet Material: Steel comp 4340 or steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, class 2 federal specification single treatment response **Thread Series Designator:**

NSN 5320-01-506-5121

Pin-rivet - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.