

View Online at <https://aerobasegroup.com/nsn/5320-01-506-5561>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Err-090

Head Height:

Between 0.228 inches and 0.238 inches

Width Between Flats:

Between 0.306 inches and 0.326 inches

Shank Diameter:

Between 0.6230 inches and 0.6240 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.918 inches and 0.953 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.9325 inches and 1.9425 inches

Thread Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.625 inches

Shear Strength:

58300 double pounds per square inch

Product Name:

Rivet

Material:

Steel comp 4340 or steel comp 4140

Material Specification:

Ams 6415 assn standard single material response or ams 6349 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0