

View Online at <https://aerobasegroup.com/nsn/5320-01-506-5706>

Thread Class:

3a

Head Style:

Flush countersunk

Shank Diameter:

Between 0.181 inches and 0.184 inches

Shank Style:

Stump

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Collar Outside Diameter:

Between 0.303 inches and 0.307 inches

Collarheight:

Between 0.437 inches and 0.457 inches

Collar Inside Diameter:

Between 0.192 inches and 0.200 inches

End Application:

Apache attack helicopter

Grip Length:

0.625 inches

Thready Qty Per Inch (tpi):

32

Minimum Yield Strength:

95000 pounds per square inch

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Collar Style:

Threaded break off type

Product Name:

Pin-riquet, assembly threaded 100 pct flush shear head

Heat Treatment:

T-6 solution heat treated collar

Material:

Stainless steel washer

Material Specification:

Qq-a-225/6 federal specification 1st material response collar or qq-a-430 federal specification 2nd material response collar

Surface Treatment:

Cadmium body

Surface Treatment Specification:

Qq-p-416, type ii, class 3, color bronze; cetyl alcohol lube federal specification single treatment response body

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.