

View Online at <https://aerobasegroup.com/nsn/5320-01-506-5889>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Err-090

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

Between 0.233 inches and 0.253 inches

Shank Diameter:

Between 0.4672 inches and 0.4682 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.615 inches and 0.650 inches

End Application:

A-10

Grip Length:

Between 1.995 inches and 2.005 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.4375 inches

Shear Strength:

32700 double pounds per square inch

Product Name:

Riquet

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.