

View Online at <https://aerobasegroup.com/nsn/5320-01-506-6528>

Thread Class:

3a

Thread Direction:

Right-hand

Head Style:

Err-090

Head Height:

Between 0.098 inches and 0.112 inches

Width Between Flats:

Between 0.160 inches and 0.180 inches

Shank Diameter:

Between 0.3266 inches and 0.3276 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.472 inches and 0.502 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.870 inches and 1.880 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.3125 inches

Shear Strength:

16000 double pounds per square inch

Product Name:

Rivet

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.