NSN 5320-01-506-9605

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-506-9605

Thread Class:	
3a	
Fastener Length:	
Between 2.073 inches and 2.0	J93 inches
Head Style:	
Flush countersunk	
Width Between Flats:	
Between 0.122 inches and 0.1	142 inches
Shank Diameter:	
Between 0.264 inches and 0.2	265 inches
Shank Style:	
Pin-rivet, straight, threaded	
Head Major Diameter:	
Between 0.502 inches and 0.5	507 inches
Lubrication:	
Cetyl alcohol, specification 30)5, hi-shear corp
End Application:	
A-10	
Grip Length:	
Between 1.683 inches and 1.6	393 inches
Thready Qty Per Inch (tpi):	
28	
Thread Size:	
0.250 inches	
Countersink Angle:	
100.0 degrees	
Product Name:	
Rivet	
Material:	
Steel comp 4340 or steel con	וף 4140 or steel comp 8740
Material Specification:	
Mil-s-5000 military specification	on single material response or mil-s-5626 military specification single material response or mil-s-6049 military
specification single material re	sponse
Surface Treatment:	
Cadmium	
Surface Treatment Specifica	ation:
Qq-p-416, type ii, class 2 fed	leral specification single treatment response
Thread Series Designator:	
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

Unit Of Measure:

NSN 5320-01-506-9605

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

