## NSN 5320-01-507-0014

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-507-0014 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.791 inches and 0.807 inches **Shank Diameter:** Between 0.1630 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches **End Application:** F-15 **Grip Length:** Between 0.9325 inches and 0.9425 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1640 inches **Shear Strength:** 5280 double pounds per square inch **Product Name:** Pin-rivet, threaded Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5320-01-507-0014

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0