

View Online at <https://aerobasegroup.com/nsn/5320-01-508-1362>

Thread Class:

3a

Fastener Length:

Between 2.073 inches and 2.093 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.122 inches and 0.142 inches

Shank Diameter:

Between 0.264 inches and 0.265 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.502 inches and 0.507 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.678 inches and 1.698 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Countersink Angle:

100.0 degrees

Product Name:

Riquet

Material:

Steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification single material response or mil-s-5626 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.