

View Online at <https://aerobasegroup.com/nsn/5320-01-509-7683>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.895 inches and 0.915 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.160 inches and 0.180 inches

**Shank Diameter:**

Between 0.3427 inches and 0.3432 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.635 inches

**End Application:**

B1-b aircraft

**Grip Length:**

0.4375 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.3125 inches

**Shear Strength:**

23200 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Pin-riquet threaded

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear spec. No. 258 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0