## NSN 5320-01-510-3432



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-510-3432 **Thread Class:** За **Thread Direction:** Right-hand **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2177 inches and 0.2182 inches **Head Major Diameter:** Between 0.3223 inches and 0.3306 inches Lubrication: Cetyl alcohol and dry film **End Application:** Aircraft, hornet f/a-18 **Grip Length:** Between 0.565 inches and 0.585 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Pin is identified on the chamfer face of the threaded end of the pin by brown dye or paint Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-510-3432

Pin-rivet - Page 2 of 2



Fiig:

A528u0