

View Online at <https://aerobasegroup.com/nsn/5320-01-511-8047>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.614 inches and 0.634 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3060 inches and 0.3220 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.307 inches and 0.317 inches

Thread Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Hi-ki=ote aluminum coating, with color light blue on thre

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard all material responses

Surface Treatment:

Aluminum

Surface Treatment Specification:

Per hi-shear specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0