## NSN 5320-01-513-2444

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-513-2444

## Thread Class:

3a

Thread Direction:

Left-hand

## Head Style:

Err-090

#### Head Height:

Between 0.044 inches and 0.056 inches

#### Shank Diameter:

0.2209 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.328 inches and 0.339 inches

## **End Application:**

C-130 aircraft

Grip Length:

Between 0.439 inches and 0.500 inches

#### Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

1400 pounds per square inch

### Thread Size:

0.138 inches

### Shear Strength:

5600 double pounds per square inch

#### **Product Name:**

Rivet blind

#### Material:

Steel comp 8740 nut

#### **Material Specification:**

Mil-s-6049 military specification single material response nut

#### Surface Treatment:

Cadmium sleeve

## Surface Treatment Specification:

Qq-p-416, type 1, class 3 federal specification single treatment response sleeve

## **Thread Series Designator:**

Uns

Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-513-2444

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

