## NSN 5320-01-513-4746

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-513-4746 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.5025 inches and 0.5225 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.012 inches and 0.015 inches **Shank Diameter:** Between 0.1890 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.298 inches and 0.303 inches Lubrication: Cetyl alcohol **End Application:** C-17 **Grip Length:** Between 0.1825 inches and 0.1925 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.1900 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Pin-rivet, threaded Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-shear spec.No. 29 (hi-kote 1 only) mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5320-01-513-4746

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0