

View Online at <https://aerobasegroup.com/nsn/5320-01-513-4746>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.5025 inches and 0.5225 inches

**Head Style:**

Countersunk w/reverse chamfer

**Head Height:**

Between 0.012 inches and 0.015 inches

**Shank Diameter:**

Between 0.1890 inches and 0.1895 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.298 inches and 0.303 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

C-17

**Grip Length:**

Between 0.1825 inches and 0.1925 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.1900 inches

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Pin-rivet, threaded

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Hi-shear spec.No. 29 (hi-kote 1 only) mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0