## NSN 5320-01-513-5644

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-513-5644

····· - ······ - ·····
Thread Class:
За
Thread Direction:
Right-hand
Head Style:
Err-090
Head Height:
Between 0.080 inches and 0.090 inches
Width Between Flats:
Between 0.094 inches and 0.096 inches
Shank Diameter:
Between 0.248 inches and 0.249 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.415 inches and 0.440 inches
End Application:
CI-125, aircraft
Grip Length:
Between 0.935 inches and 0.955 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
9300 double pounds per square inch
Material:
Titanium alloy
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5320-01-513-5644

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

