## NSN 5320-01-513-5647

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-513-5647

····· - ······ ····
Thread Class:
За
Thread Direction:
Right-hand
Head Style:
Err-090
Head Height:
Between 0.055 inches and 0.065 inches
Width Between Flats:
Between 0.079 inches and 0.080 inches
Shank Diameter:
Between 0.162 inches and 0.163 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.306 inches and 0.322 inches
End Application:
CI-125, aircraft
Grip Length:
Between 0.582 inches and 0.602 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.165 inches
Shear Strength:
4010 double pounds per square inch
Material:
Titanium alloy
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5320-01-513-5647

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

