# NSN 5320-01-513-6510

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-513-6510



# Thread Class: 3a Thread Direction:

Right-hand

#### Head Style:

Err-090

# Head Height:

Between 0.064 inches and 0.074 inches

# Width Between Flats:

Between 0.079 inches and 0.096 inches

#### Shank Diameter:

Between 0.217 inches and 0.218 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.370 inches and 0.390 inches

#### **End Application:**

Cl-125, aircraft

# Grip Length:

Between 0.915 inches and 0.935 inches

# Thready Qty Per Inch (tpi):

32

# Min. Tensile Strength (psi):

160000 pounds per square inch

# Thread Size:

0.191 inches

# Shear Strength:

7100 double pounds per square inch

# Material:

Titanium alloy

# Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

# Surface Treatment:

Aluminum

# **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-513-6510

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

