# NSN 5320-01-514-3377

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-514-3377



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.760 inches and 0.780 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.080 inches and 0.090 inches

#### Width Between Flats:

Between 0.122 inches and 0.142 inches

#### Shank Diameter:

Between 0.2802 inches and 0.2807 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.435 inches and 0.480 inches

#### Lubrication:

Cetyl alcohol

#### **End Application:**

C-17a aircraft

#### Grip Length:

Between 0.370 inches and 0.380 inches

#### Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

#### **Product Name:**

Pin-rivet, threaded

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

#### Surface Treatment:

Aluminum

## Surface Treatment Specification:

Hi-shear spec.No.29 (hi-kote 1 only) mfr ref single treatment response

# Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5320-01-514-3377

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

