

View Online at <https://aerobasegroup.com/nsn/5320-01-514-3381>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.198 inches and 1.218 inches

Head Style:

Err-090

Head Height:

Between 0.010 inches and 0.015 inches

Width Between Flats:

Between 0.122 inches and 0.142 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

Head Minor Diameter:

Between 0.375 inches and 0.388 inches

Countersink Height:

Between 0.069 inches and 0.076 inches

Lubrication:

Cetyl alcohol

End Application:

C-17a aircraft

Grip Length:

Between 0.8075 inches and 0.8175 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Countersink Angle:

100.0 degrees

Product Name:

Pin-rivet, threaded

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4967 assn standard single material response or ams 4928 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear spec.No.29 (hi-kote 1 only) mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0