

View Online at <https://aerobasegroup.com/nsn/5320-01-515-1283>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 3.543 inches and 3.563 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.221 inches and 0.224 inches

Shank Diameter:

Between 0.514 inches and 0.515 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.735 inches and 0.770 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.808 inches and 1.818 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

125000 single pounds per square inch

Product Name:

Pin-rivet threaded

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0