

View Online at <https://aerobasegroup.com/nsn/5320-01-515-1781>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.755 inches and 2.775 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.255 inches and 0.265 inches

**Width Between Flats:**

Between 0.252 inches and 0.256 inches

**Shank Diameter:**

Between 0.654 inches and 0.655 inches

**Head Major Diameter:**

Between 0.935 inches and 0.970 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

A-10

**Grip Length:**

Between 1.870 inches and 1.880 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

210000 pounds per square inch

**Thread Size:**

0.625 inches

**Shear Strength:**

125000 single pounds per square inch

**Product Name:**

Pin-rivet threaded

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0