

View Online at <https://aerobasegroup.com/nsn/5320-01-515-2070>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.565 inches and 2.585 inches

Head Style:

Err-090

Head Height:

Between 0.228 inches and 0.238 inches

Width Between Flats:

Between 0.252 inches and 0.256 inches

Shank Diameter:

Between 0.623 inches and 0.624 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.918 inches and 0.953 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

A-10

Grip Length:

Between 1.745 inches and 1.755 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

54600 pounds per square inch

Thread Size:

0.625 inches

Shear Strength:

125000 single pounds per square inch

Product Name:

Pin-riquet threaded

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type ii, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0