

View Online at <https://aerobasegroup.com/nsn/5320-01-515-2483>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.628 inches and 2.648 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.228 inches and 0.238 inches

**Width Between Flats:**

Between 0.252 inches and 0.256 inches

**Shank Diameter:**

Between 0.654 inches and 0.655 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.940 inches and 0.975 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

A-10

**Grip Length:**

Between 1.808 inches and 1.818 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

54600 pounds per square inch

**Thread Size:**

0.625 inches

**Shear Strength:**

125000 single pounds per square inch

**Product Name:**

Pin-rivet

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0