## NSN 5320-01-515-8979

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-515-8979 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.530 inches and 2.550 inches **Head Style:** Err-090 **Head Height:** Between 0.200 inches and 0.210 inches Width Between Flats: Between 0.306 inches and 0.326 inches **Shank Diameter:** Between 0.5922 inches and 0.5927 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.870 inches and 0.905 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** A-10 **Grip Length:** Between 1.745 inches and 1.755 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 0.5625 inches **Shear Strength:** 69200 double pounds per square inch **Product Name:** Hy-lok Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5320-01-515-8979

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0